

REVOTIK 2GE +1POTS ROUTER

Revotik RVXPON302WAC terminal devices are designed for fulfilling FTTH and triple play service demand of fixed network operators or cable operators. These boxes are based on the mature Chipset (Realtek) technology, which have high ratio of performance to price, and Layer 2/3, and high-quality VoIP as well.

They are highly reliable and easy to maintain, with guaranteed QoS for different service. And they are fully compliant with technical regulations such as ITU-T G.984.x and technical requirement of GPON.



SPECIAL FEATURES

MANAGEMENT MODE

- OAM/OMCI, Telnet, WEB, TR069

DATA SERVICE FUNCTIONS

- Full speed non-blocking switching
- 2K MAC address table
- 64 full range VLAN ID
- Support QinQ VLAN, 1:1 VLAN, VLAN reusing, VLAN trunk
- Integrated port monitoring, port mirroring, port rate limiting, port SLA, etc
- Support auto polarity detection of Ethernet ports (AUTO MDIX)
- Integrated IEEE802.1p QoS with four level priority queues
- Support IGMP v1/v2/v3 snooping/proxy and MLD v1/v2 snooping/proxy
- Support bridge, router and bridge/router mixed mode

POTS SERVICE FUNCTION

- Call protocol: SIP(IMS compatible) seamless compatible with all popular call agent
- Integrate heartbeat function and support active/standby call agent
- Voice coding: ITU-T G.711/G.722/G.729, auto-negotiate with call agent
- Echo cancellation exceeding ITU-T G.165/G.168-2002, up to 128ms tail length
- Support high/low speed fax, bypass fax, and T38 fax
- Support high speed MODEM(56Kbps) dial access
- Support RFC2833 and redundant RFC2833, difference rings, MD5 authentication, call forward, call waiting, hot-line call, alarm clock, and all kinds of value-added voice service
- Multi-party conferencing
- IP address assignment: dynamic PPPoE/DHCP Client and static IP
- Support WEB, CLI, IVR, TR069
- Call loss less than 0.01%

TECHNICAL PARAMETERS

MODEL	RVXPON302WAC
PON interface	1 GPON port Receiving sensitivity: ≤-28dBm Transmitting optical power: 0~+4dBm Transmission distance: 20KM
Wavelength	Tx1310nm,Rx 1490nm
Optical interface	SC/APC connector
LAN interface	2 x 10/100/1000Mbps auto adaptive Ethernet interfaces, Full/Half, RJ45 connector
POTS interface	1 x RJ11 connectors Support: G.711A/G.711U/G.723/G.729 codec Support: T.30/T.38/G.711 Fax mode, DTMF Relay
LED	10, For Status of POWER, LOS, PON, SYS, LAN1~LAN2, POTS,
Operating condition	Temperature: 0℃~+50℃, Humidity: 10%~90% (non-condensing)